



Kerapoxy Cleaner

Special cleaning solution for epoxy grout



WHERE TO USE

Kerapoxy Cleaner is a detergent used to remove traces of epoxy grout such as **Kerapoxy**, **Kerapoxy P**, **Kerapoxy Design**, etc. from ceramic and glass mosaic coatings.

Some application examples

- Removal of epoxy grout residues whether small or large from the surface of ceramic and glass coatings.
- Cleaning of the tile/mosaic surface grouted with **Kerapoxy**, **Kerapoxy P**, **Kerapoxy Design**, etc. after completion of grouting.

TECHNICAL CHARACTERISTICS

Kerapoxy Cleaner is a concentrated liquid detergent for epoxy grout. **Kerapoxy Cleaner** is used to remove residues, stains and marks of epoxy grout without giving off hazardous fumes.

If used correctly, **Kerapoxy Cleaner** does not damage either the tile/mosaic surface or grouted joints.

RECOMMENDATIONS

- Do not use on polished marble or stone.
- Do not use on wood.
- Do not use on methacrylate pools.
- Before using **Kerapoxy Cleaner** on materials with an unknown surface resistance, test the product beforehand to make sure it does not damage the surface.

- Before using the product, protect all surfaces which could be damaged in direct contact with the product.

APPLICATION PROCEDURE

Apply **Kerapoxy Cleaner** on the surface to be cleaned or on the traces of grout and leave standing for a few minutes. Then rub the surface with a Scotch-Brite® pad and rinse thoroughly with water. The product is particularly efficient on fresh grout. If cleaning is carried out a few hours after applying the grout, it may be necessary to leave it standing for longer (at least 15-20 minutes), or repeat the cycle.

PACKAGING

Kerapoxy Cleaner is available in 0.75 kg spray bottles and 5 kg canisters.

STORAGE

Kerapoxy Cleaner may be stored for up to 24 months in its original, sealed packaging in a cool place.

SAFETY INSTRUCTIONS FOR PREPARATION AND APPLICATION

Kerapoxy Cleaner is irritant for the eyes. During use wear safety gloves and goggles and take the usual precautions for handling chemicals. In case of contact with the eyes or the skin, wash immediately with plenty of water and seek medical attention.

For further and complete information about the safe use of our product please refer to the latest version of our Material Safety Data Sheet.

PRODUCT FOR PROFESSIONAL USE.

Kerapoxy Cleaner



Spraying Kerapoxy Cleaner on the surface requiring cleaning



Cleaning with a Scotch-Brite® pad



Final rinsing with a sponge

TECHNICAL DATA (typical values)	
PRODUCT IDENTITY	
Consistency:	liquid
Colour:	transparent straw yellow
Density (g/cm ³):	1.010
pH:	10
APPLICATION DATA (at +23°C and 50% R.H.)	
Application temperature range:	from +5°C to +35°C
Waiting time before rinsing:	from a few minutes with fresh grout, up to 4 hours for more difficult residues

Ingredients in compliance with Regulation EC No. 648/2004. Between 5% and 15% soap, perfumes, Limonene, Linalool.

WARNING

Although the technical details and recommendations contained in this product data sheet correspond to the best of our knowledge and experience, all the above information must, in every case, be taken as merely indicative and subject to confirmation after long-term practical application; for this reason, anyone who intends to use the product must ensure beforehand that it is suitable for the envisaged application. In every case, the user alone is fully responsible for any consequences deriving from the use of the product.

Please refer to the current version of the Technical Data Sheet, available from our website www.mapei.com

LEGAL NOTICE

The contents of this Technical Data Sheet ("TDS") may be copied into another project-related document, but the resulting document shall not supplement or replace requirements per the TDS in force at the time of the MAPEI product installation.

The most up-to-date TDS can be downloaded from our website www.mapei.com.

ANY ALTERATION TO THE WORDING OR REQUIREMENTS CONTAINED OR DERIVED FROM THIS TDS EXCLUDES THE RESPONSIBILITY OF MAPEI.

All relevant references for the product are available upon request and from www.mapei.com



Cleaning the surface of the coating after laying



BUILDING THE FUTURE