

Product name	:	Glue Spray	
Article number	:	28 571	
Exclusive Distributor	:	Fournarakis S.A.	
		9.5 klm Attiki Odos exit 4	Aspropyrgos Athens Greece
		Telephone number +	⊦ 30 210 55 98 400
		Telefax number	+ 30 210 55 98 440
		Made in Holland	

Product description

High quality glue for both permanent and temporary adhesion. Suitable to glue paper, cardboard, wood, textile and various types of plastic.

Applications

Paper Wood Cork Locks Various types of plastic Cardboard Textile Leather Garden tools

Product characteristics

Suitable to glue large surfaces Fast drying User-friendly Spray pattern about 10 centimetre wide

Physical and Chemical Characteristics

Contents Basis VOC-content Colour Scent Yield Relative density at 20°C Vapour pressure at 20°C Heat resistant : 400 ml
: Synthetic resin
: Approximately 83% w/w
: Transparent white
: Characteristc
: 1,2 g /sec
: 0,75 g/ml
: 3 to 4 bar
: to 80°C

Usage Before use, carefully read the direct ions on the packaging and act accordingly.

The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 5 to 30° C. Before use, shake the aerosol. Distance to the surface to be treated approximately 25 to 30 centimetre.

Apply glue in an equal layer.

For a permanent adhesion treat both parts to be glued, allow to dry 15 to 20 minutes and firmly press together.

For a temporary adhesion treat one of the parts to be glued, allow to dry for 5 to 10 minutes, and firmly press together.

When treating porous surfaces, apply several layers.

After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

